


Wired IO Module flush-mount – 6 channels



VDE certified

Product ref.: 152482A0



Product features

- Connects push-button inputs and LED outputs with the Homematic IP Wired system via the bus
- Six inputs and outputs offer comfortable and individual connection of push-buttons, switches, contacts (e.g. reed contacts in windows) as well as LEDs
- Enables bus installations outside the main or sub-distribution using flush-mounted or surface-mounted boxes
- Corrosion protection prolongs the lifetime of connected push-buttons and switches
- For operation within the Wired system, a Homematic IP Wired Access Point is required. The Wired system offers control via the Central Control Unit CCU3, many partner solutions as well as the Homematic IP cloud service (coming soon).

Technical specifications

| | |
|--|---|
| Supply voltage | 24 VDC, +5 %, SELV |
| Current consumption | 150 mA max./2.5 mA (typically) |
| Standby power consumption | 60 mW |
| Outputs | |
| Quantity | 6 |
| Voltage | 24 Vdc, SELV |
| "0" signal | voltage-free |
| "1" signal | 24 V, max. 20 mA |
| Line length | < 30 cm |
| Input | |
| Quantity | 6 |
| Signal voltage | 24 Vdc, SELV |
| "0" signal | 0 to 14 VDC |
| "1" signal | 18 to 24 VDC |
| Signal current | 3,2 mA |
| Signal duration | (corrosion protection: approximately 125 mA) at least 80 ms |
| Maximum line length | < 30 m |
| Cable type and cross section for bus connection | rigid cable, 0.12-0.5 mm ² |
| Installation | only in switch boxes (device boxes) in accordance with DIN 49073-1 or surface-mounting boxes in accordance with DIN 60670-1 (e.g. Abox 025 or Abox 040) |
| Degree of protection | IP20 |
| Ambient temperature | -5 to +40 °C |
| Dimensions (ø x H) | 57 x 14 mm |
| Weight | 20 g |

Logistical data

| | |
|------------------------|------------------|
| Product reference | 152482A0 |
| EAN code | 4047976524822 |
| Short description | HmiPW-FIO6 |
| Packing unit | 144 |
| Packing dimensions | 122 x 93 x 36 mm |
| Weight incl. packaging | 90.0 g |

Package contents

Homematic IP Wired IO Module flush-mount – 6 channels

Connecting cable for inputs and outputs (2x)

User manual